INSTALLATION - SERVICE INSTRUCTIONS



SERVICE BULLETIN

NO. 0041 PAGE 1 OF 1

QUICK RELEASE HUBS

JANUARY 24, 1995

765 South Pierce Avenue, Louisville, CO 80027 (303) 665-6901 / 800-525-1963

PART NUMBER: DESCRIPTION:

ALL MW QUICK RELEASE HUBS MEETS S.F.I. SPEC 42.1.

10020 QUICK RELEASE HUB FOR DRAGSTER/FUNNY CAR

10025 Quick release hub for 5 hole Grant steering wheel (3/16" holes, 5 x 2.86 bolt circle)

10060 QUICK RELEASE HUB FOR 3 HOLE DON LONG STEERING WHEEL (10-32 THREADS)
10070 QUICK RELEASE HUB FOR 3 HOLE OVAL TRACK (1/4" THREADS ON 1.75 BOLT CIRCLE)
10075 QUICK RELEASE HUB FOR 3 HOLE OVAL TRACK (5/16" THREADS ON A 1.75 BOLT CIRCLE)

10080 QUICK RELEASE HUB, UNIVERSAL (NO HOLES)

PART INCLUDED:

1-HUB, 1-SPLINED SLEEVE, 1-RELEASE SLEEVE, 3- BALL BEARINGS, 1 SPRING, AND MOUNTING HARDWARE.

PRIMARY APPLICATION:

ANY.

INSTALLATION OVERVIEW:

- 1) TURN WHEELS STRAIGHT, REMOVE OLD WHEEL.
- 2) Place splined steering shaft with 1-tooth omitted on steering column. Locate 1-tooth omitted serration and place at 12:00 O'clock for easy steering indexing.
- 3) BOLT OR WELD SPLINED SHAFT TO STEERING COLUMN.
- 4) BOLT STEERING WHEEL TO QUICK RELEASE HUB.

