

9" FORD COMPONENTS



| | | | | | |
|----------|-----------------------------------------------------------------------------|--------|----------|------------------------------------------------------------------------|-------|
| 39008 | MW 9" Ford Pinion Yoke | 165.00 | 57608 | Bolt Kit, 9" Ford Pinion Support | 6.30 |
| | <i>28-spline, 4340 steel for 1350 series U-joint.</i> | | 57609 | Stud Kit, 9" Ford Pinion Support | 44.00 |
| 39011 | MW 9" Ford Pinion Yoke | 165.00 | | <i>For stock and non M-W cases.</i> | |
| | <i>35-spline, 4340 steel for 1350 series U-joint.</i> | | 57900 | Ring Gear Bolt Set (7/16") | 34.00 |
| 39025 | 9" Ford Pinion Yoke 1330 Ford Joint | 175.00 | | <i>Drilled for safety wire (use ARW77 washers w/Strange spool)</i> | |
| | <i>4340 steel for Ford 1330 series joint 3-5/8 x 1-1/8" for MW support.</i> | | 57901 | Gasket, 9" Ford Thirdmember | 3.50 |
| 5000-181 | Retaining Ring For MW Ford Case | 1.25 | 57901-TS | 9" Ford Thirdmember Gasket | 7.70 |
| 53124 | 9" Ford Spool Bearings 3.812 O.D. | 80.00 | | <i>EZ-Release reusable gasket.</i> | |
| 53141 | 9" Ford Spool Bearings, 2.893 O.D. | 53.15 | 57902 | Pinion Nut, 9" Ford (standard pinion) | 4.50 |
| 53142 | 9" Ford Spool Bearings, 3.062 O.D. | 61.45 | 57903 | Pinion Nut, 9" Ford (35 spline pinion) | 4.75 |
| 53143 | 9" Ford Spool Bearings, 3.250 O.D. | 59.30 | 57904 | Seal, 9" Ford Pinion (standard pinion) | 13.50 |
| 57407 | Pinion Stud Kit for MW Cases 7/16" | 51.00 | 57905 | Seal, 9" Ford Pinion (35 spline pinion) | 15.30 |
| 57408 | Pinion Stud Kit for MW Case 3/8" | 43.00 | 57906 | Adjuster Locks(pr) | 5.50 |
| 57449 | Load Bolt Kit for MW Case | 29.85 | 57907 | Pinion Pilot Bearing (MW cases, Long) | 16.75 |
| 57500 | Heavy-Duty Adjusters, 3.062 bore | 54.00 | 57908 | Pilot Bearing Retainer (for stock case) | 8.00 |
| 57502 | Replacement Cap, 2.893" bore (ea) | 90.00 | 57909 | Crush Sleeve (stock support) | 10.00 |
| 57503 | Replacement Cap, 3.062" bore (ea) | 90.00 | 57912 | Seal, 9" Ford Pinion (40 spline pinion) | 31.80 |
| 57510 | Shim, Spool/Carrier (pr) | 48.15 | | <i>For 57650 or 11"pinion support Viton high temperature compound.</i> | |
| | <i>For 9" Ford Spool/Carrier in a 3-1/4" case.</i> | | 57913-10 | Thirdmember Stud Kit (10 ea.) | 63.21 |
| 57550 | Heavy-Duty Adjusters, for 3.250 bore (pr) | 62.00 | | <i>Thirdmember to housing attachment bolts, nuts and washers.</i> | |
| 57560 | Heavy-Duty Adjusters, for 3.812 bore (pr) | 94.50 | 57914 | Pinion Pilot Bearing, .812" Long | 19.60 |
| 57570 | Adjuster Adapter (pr) | 103.64 | | <i>For MW thru bolt cases.</i> | |
| | <i>To use 3.062" bearing in a 3.25" case, (best method).</i> | | 57916 | 9" Pinion Depth Shims .005"-.015" | 15.75 |
| 57602 | Pinion Bearing Sleeve | 15.25 | | <i>MW alum. shims. 2ea-.005, .007 & 1 ea-.010, .012, .015.</i> | |
| | <i>For rear bearing of 57600/57620 Pinion Bearing Housing.</i> | | 57920 | Ring Gear Bolt set (1/2") | 55.00 |
| 57603 | Solid Pre-Load Spacer | 18.50 | | <i>Drilled for safety wire (use ARW78 washers w/Strange spool)</i> | |
| | <i>For 57600, 57610, 57620 and 57630 (machining required).</i> | | TRD-3244 | Pinion Bearing Shim | 10.25 |
| 57604 | Shim, Yoke/Coupler | 11.00 | | <i>Required with 57602 sleeve.</i> | |
| | <i>For use with 39008 or 40300 with stock 9" Ford pinion housing.</i> | | 57999 | Thirdmember Transport Container | 58.75 |

9" FORD AXLE & SPOOL PACKAGE



The MW 9" Ford Axle/Spool Package includes a pair of custom built standard Hi-Torque axles (any length/35 or 40 spline combination), axle bearings, bearing retainer plates, standard steel spool and a complete 5/8 drive stud kit with Snap-Lock™ washers This kit allows you to have the top of the line axle and spool kit while saving 10%.

HI-K12 Axles/Spool/Bearing/Retainer/Stud Kit1015.75
9" Ford spool, axle and drive stud kit

Call for additional savings on a lightweight components package.

toll free
800-525-1963

on the web
www.markwilliams.com