FULL FLOATER HUB KITS



The MW Full Floater assembly is required by most sanctioning bodies for Fuel, Alcohol, and Pro Modified racecars. In the event of an axle failure, the floating hub will prevent wheel loss. An added performance advantage is that the wheel alignment is maintained under high acceleration load situations, preventing a "toe in" condition. The Series II floater assemblies feature a handful of new improvements. A larger inside bearing allows thicker spindle cross-section preventing crack propagation under severe tire-shake conditions. The forged aluminum hub has improved stud retention with deeper counter-bores and longer threads engagement. Hubs are available with either 4-3/4", 5" or 5-1/2" X 5 hole bolt circle. Spindles are produced from forged 4340 chrome-nickel-molybdenum steel and heat-treated. Floater axles are available in the standard 4340 or 300M, solid or gun-drilled. Drive plates are 40-spline and heat-treated alloy steel or aluminum drive pates with steel spline insert as a option.

Kits are available with conventional steel rotors or carbon-carbon setups that feature our Slot-DriveTM rotor attachment technology. Upgrade options include ceramic wheel bearings and four caliper brake kits. The floater kits are also available with long spindles, or without spindles to fit modular housings already equipped with spindles.

STANDARD FLOATER KITS

Kits Without Spindles 95475 Full Floater Hub Assembly	Complete Kits 95470 Full Floater Hub Assembly
95750 Full Floater Hub Assembly	95700 Full Floater Hub Assembly
95850 Full Floater Hub Assembly	95800 Full Floater Hub Assembly
CA	RBON/CARBON FLOATER KITS
95485 Full Floater Hub Assembly, Carbon	95480 Full Floater Hub Assembly, Carbon 7308.00 40 spline axles, 4-3/4" x 5" bolt pattern.
95450 Full Floater Hub Assembly, Carbon	95400 Full Floater Hub Assembly, Carbon
95570 Full Floater Hub Assembly, Carbon	95555 Full Floater Hub Assembly, Carbon7308.00 40 spline axles, 5 x 5" bolt pattern.
	FLOATER KIT OPTIONS
11-3/8" Diameter Disc for 15" WheelsP.O.A.	Floater Axles (non-standard lengths*)P.O.A.
Dual Caliper Option (4 Caliper)	Long Spindle UpgradeP.O.A.
Titanium Wheel StudsP.O.A.	Ceramic Bearing upgradeP.O.A.
Aluminum Lug NutsP.O.A.	Aluminum Drive Plates upgrade
300M Material Axle Shafts gun drilledP.O.A.	* Stocked axle lengths are for 32" to 38" wheel to wheel

toll free 800-525-1963

on the web